

DESCRIPTION

Dual Power Amplifier TOA DA-Z250D model is a highly efficient two channels power amplifier for the purposes of sound system or music background in the multipurpose room / hall, restaurants, place of worship or rooms that require high-quality sound system.


SPECIFICATIONS

| | |
|--------------------|--|
| Power Source | 220 - 240 V AC, 50/60 Hz |
| Amplifier System | Digital class D |
| Power Consumption | 120 W (EN Standard), 620 W (rated 4Ωx2), 400 W (rated 8Ωx2) |
| Frequency Response | 20 - 20,000 Hz, ±1 dB |
| Distortion | Less Than 0.3% at 1 kHz, 1/3 Output rated |
| Input | 2 channels, +4 dBm* (1.23 V, on the position of the maximum volume control), 10kΩ, Electronically balanced, XLR connector Parallel switch ON/OFF CH1 (ON : Parallel, OFF : each CH) |
| Output | 2 channels : 250 W x 2 (4Ω), 170 W x 2 (8Ω) 1 channel : 500 W (8Ω), BRIDGE |
| Protection Series | Protection for over-current when the load is beyond the specifications, short-circuit, unnecessary DC voltage protection, and protection due to the increased excessive heat |
| S/N Ratio | More than 80 dB |
| Cooling System | Cooling fan |
| Indicator Led | Power (Green) x 1, Input (Green) x 2, Output (Yellow) x 2, Peak (Red) x 2, Protect (Red) x 2 |
| Finish | Front Panel : Aluminum Hair Line, Etching Black Case : Steel Plate, Painting Black |
| Dimensions | 420 (W) X 59.5 (H) X 345 (D) in mm |
| Weight | 4.5 kg |
| Accessory | AC Power cord 2 meters |

Note : *) 0 dBm = 0.775 V

**) Specification is measured at the AC voltage of 230V.

APPEARANCE



UNIT : mm SCALE : 1/3